

Honeywell

[Honeywell.com](http://honeywell.com)
[HOME](#)
[ABOUT US](#)
[PRODUCTS](#)
[OEM-SOLUTIONS](#)
[CONTACT US](#)

Wireless room thermostat for heating



The wireless room thermostat HCW80 sends heat demand signals (RF 868,3 MHz) to the relay module HC60NG. It can be used to control gas and oil boilers, a variety of valves and actuators, or electrical heating systems.

Approvals	EN60730-1, EN55014-1, EN55014-2, ETSI EN300220-3, ETSI EN301489
RF communication distance	30 m
Blocking immunity	Receiver class 2 (EN300220-1)
Batteries	included 2 x AA
Battery life	2 years typical
LED functions	heat demand on/off, battery status
Housing (HxWxD)	105 mm 98 mm 30 mm
Protection class	IP30
Temp. setpoint range	5 ... 30 °C
Additional description	Setpoint scale with frost protection symbol and small pins for limitation of the adjustment range.

Product description	Type
Room thermostat	HCW80

Package	Type
Product description	
1x HCW80, 1x R6660D009	Y6630D1007

HC60NG Relay box	Additional Product Type
Description	
Relay box (1-off) with English and German literature	R6660D1009

[Privacy Statement](#) | [Terms and Conditions](#) | [Imprint](#)

Copyright Honeywell Inc. 2011

[Combustion Solution](#)
[HVAC Solutions](#)