

Honeywell

Honeywell.com

HOME

ABOUT US

PRODUCTS

OEM-SOLUTIONS

CONTACT US

Digital room thermostat, DT90



Digital non-programmable thermostat with large LCD display and simple user interface. For general purpose control of boilers, zone valves, pumps, thermal actuators, electric heaters and fan-coil units.

- self-learning TPI Fuzzy logic control
- adjustable proportional band
- adjustable on/off time
- frost protection
- setpoint limits
- fail-safe operation
- installer mode

Approvals	CE
Protection class	IP30
Switch function/capacity	SPDT 24..230 Vac, 8 A resistive, 3 A inductive; potential free
Power source	battery powered, 2 x 1,5 V AA Alkaline cells
Battery life	minimum 2 years
Terminal max. wire size	2,5 mm ²
Temp. setpoint range	5 ... 35 °C
Control output signal	on/off
Manual operation functions	-off/standby, -setpoint, -ECO
Heat/Cool manual mode	H/C
Product literature language	multilanguage user guide included in package
Earthing	double insulated
Housing (HxWxD)	92 mm 90 mm 27 mm

Model	Type
standard	DT90A1008
with ECO button for up to 24h energy-saving setback	DT90E1012

[Privacy Statement](#) | [Terms and Conditions](#) | [Imprint](#)

Copyright Honeywell Inc. 2011

Combustion Solution
HVAC Solutions