

Honeywell

[Honeywell.com](http://honeywell.com)
[HOME](#)
[ABOUT US](#)
[PRODUCTS](#)
[OEM-SOLUTIONS](#)
[CONTACT US](#)

Wireless room thermostat, DT92



Room thermostat and relay box, with 2-way RF-communication between these units. The thermostat is non-programmable; it has a large LCD display and simple user interface. For general purpose control of boilers, zone valves, pumps, thermal actuators, electric heaters and fan-coil units.

- self-learning TPI Fuzzy logic control
- adjustable proportional band
- adjustable on/off time
- frost protection
- setpoint limits
- fail-safe operation
- installer mode
- transmission and signal strength features

Approvals	CE
Protection class	IP30
Switch function/capacity	relay box with SPDT-switch 24..230 Vac, 5 A resistive, 3 A inductive; potential free
Power source	<ul style="list-style-type: none"> • relay box: 230 V, 1 VA • thermostat: battery powered, 2 x 1,5 V AA Alkaline cells
Battery life	minimum 2 years
Terminal max. wire size	2,5 mm ²
Temp. setpoint range	5 ... 35 °C
Control output signal	on/off
Manual operation functions	-off/standby, -setpoint, -ECO
Display functions	thermostat: <ul style="list-style-type: none"> • room temperature, setpoint, off/standby mode, relay status, RF communication, ECO mode and countdown • frost protection, internal fault, battery low, loss of RF communication
LED functions	relay box: <ul style="list-style-type: none"> • green LED for relay on/off status, transmission test • red LED for status in RF binding or reset modes, loss of RF communication
Product literature language	multilanguage user guide included in package
Earthing	double insulated
Housing (HxWxD)	92 mm 90 mm 27/30,5 mm

Thermostat with relay box

Model	Type
standard	DT92A1004
with ECO button for up to 24h energy-saving setback with adjustable setpoint	DT92E1000

[Privacy Statement](#) | [Terms and Conditions](#) | [Imprint](#)

Copyright Honeywell Inc. 2011

Combustion Solution
HVAC Solutions