

NEW
WITH BLUETOOTH®



Pressing Unit ACO103

-  Metal up to 35 mm
Plastic up to 40 mm
-  One-Hand-Operation
-  Status indication with LED display
-  Illumination of the press area
-  Data transfer via Bluetooth®

Compact and high-performance efficiency

- Powerful Milwaukee Lithium-Ion batteries for reliable performance
- Redundant switch-off and press force control with LED indication
- Automatic pressing cycle
- Safe handling with slipproof rubberized housing and ergonomic design
- Illumination of the press area for safe working
- Analysis of the pressing tool performance via NovoCheck app



Press jaw PB1

Pressing Unit ACO103

Compact and high-performance efficiency

The pressing unit ACO103 has many valuable features to make working easier, faster and safer. The LED signal located under the transparent start button gives information about the battery and the status of the pressing unit or occurred failures. Thanks to the new, implemented Bluetooth®-Technology, device-related data can be requested via the NovoCheck app.

NovoCheck-App

- Data transfer between pressing tool and app
- Possibility to check the pressing tool's current status
- Analysis of the pressing tool performance
- Integrated report function for documentation of the installation



Scope of application

- Drinking water-, gas- and heating installations, industry and commercial applications and many more
- Suitable for all authorized jaws of other system manufacturers in the market*
- All common profiles for metal and plastic systems available

Accessories

- Press jaws PB1
- Charger available in many worldwide power supply specifications
- Batteries with different capacities available



The LED signal located under the transparent start button gives information about the battery and the status of the pressing units or occurred failures.



Novopress quality and service

Tool features

- Battery-empty-detection
- Error display
- Device information through the LED indication under the start button
- Automatic pressing cycle
- Electronic bolt retention

Maintenance and service

- Qualified service on site thanks to international service network
- Mobile on-site service thanks to our service vehicle in Germany and parts of Europe
- Extended warranty (further information at www.novopress.de)

Technical Data ACO103

Dimensions**:	Metal pipe up to 35 mm / Plastic pipe up to 40 mm
Weight incl. Battery:	1.7 kg
Length:	320 mm
Width:	98 mm
Height:	72 mm
Power consumption:	240 W
Piston force:	19 kN
Piston stroke:	30 mm
Battery:	12 V / 1.5 Ah Li-Ion Milwaukee 12 V / 3.0 Ah Li-Ion Milwaukee
Battery capacity***:	40 - 180 press cycles
Charging time:	30 / 60 min.

* for binding information please request your system manufacturer

** system-dependant

*** depending on material and dimension

We reserve the right to make technical modifications.

novopress

Novopress GmbH Pressen und Presswerkzeuge & Co. KG
Scharnhorststraße 1 · 41460 Neuss · Germany
Tel.: +49(0)2131-288-0 · Fax: +49(0)2131-288-55
www.novopress.de · E-Mail: verkauf@novopress.de