



Pressing Unit ACO203

powered by Brushless Motor Technology

Fit for the future with the new tool generation

- Light-weight and handy
- Up to 40 % more pressings per battery charge*
- Illumination of the press area for safe working
- Reduced need for maintenance due to new motor technology
- Maintenance interval of 2 years - without limited numbers of press cycles
- Analysis of the pressing tool performance via NovoCheck app

Compatible press jaws and collars



Illumination of the press area



Metal up to 54 mm (M-Contour)
up to 108 mm (V-Contour)
Plastic up to 110 mm



Low weight



Small tool dimensions



Data transfer via Bluetooth®

novopress
because quality matters

* in comparison to its predecessor ACO202

Pressing Unit ACO203

The future in hand - Press technology of a new generation
Efficient - the ACO203 offers all features needed for economic and efficient working. The innovative Brushless Motor Technology is impressive with its high performance and its low need for maintenance. Thanks to the new, implemented Bluetooth® technology, device-related data can be requested via the NovoCheck app.

NovoCheck app

- Data transfer between pressing tool and app
- Possibility to check the pressing tool's current status
- Analysis of the pressing tool performance
- Integrated report function for documentation of the installation



Scope of application

- Drinking water-, gas- and heating installations, industry and commercial applications and many more
- Suitable for all authorized jaws of other system manufacturers in the market*
- All common profiles for metal and plastic systems available

Accessories

- Press jaws PB2
- Press collars with adaptor jaw ZB202 / ZB203
- Charger available in many worldwide power supply specifications
- Batteries with different capacities and implemented battery-status-indication available

The implemented illumination of the press area makes working, even in difficult lighting conditions, easier.



Novopress quality and service

Tool features

- Battery-empty-detection
- Error display
- Device information through the LED indication under the start button
- Automatic pressing cycle

Maintenance and service

- Qualified service on site thanks to international service network
- Mobile on-site service thanks to our service vehicle in Germany and parts of Europe
- Extended warranty (further information at www.novopress.de)



Technical Data ACO203

Dimensions:	Metal pipe up to 54 mm (M-Contour), resp. up to 108 mm (V-Contour) / Plastic pipe up to 110 mm
Weight incl. Battery:	2.8 kg
Length:	387 mm
Width:	75 mm
Height:	111 mm
Power consumption:	450 W
Piston force:	32 kN
Piston stroke:	40 mm
Battery:	18 V Li-Ion / 1.5 Ah Milwaukee 18 V Li-Ion / 3.0 Ah Milwaukee
Battery capacity**:	up to 250 press cycles
Charging time:	approx. 30 - 60 min.

* for binding information please request your system manufacturer
** depending on material and dimension

We reserve the right to make technical modifications.

novopress

Novopress GmbH Pressen und Presswerkzeuge & Co. KG
Scharnhorststraße 1 · 41460 Neuss · Germany
Tel.: +49(0)2131-288-0 · Fax: +49(0)2131-288-55
www.novopress.de · E-Mail: verkauf@novopress.de