

# I-50

Radius: **13.1 to 23.2 m**  
Flow: **1.63 to 6.84 m<sup>3</sup>/hr; 27.2 to 114.1 l/min**

The high-torque I-50 rotor is engineered to thrive in difficult water-quality conditions within large turf projects.

## KEY BENEFITS

- Extra-strong, non-strippable, planetary gear drive mechanism is reliable and durable in harsh water conditions
- Tool-free, part- and full-circle arc adjustment mechanism makes fast, easy installation and reduces inventory (60° to 360°)
- Colour-coded nozzles make identification easy
- Available opposing nozzle model for even watering in full-circle applications (I-50-ON model)
- Drain check valve prevents low-head drainage (up to 4.5 m of elevation)

## OPERATING SPECIFICATIONS

- Nozzle choices: 12
- Radius I-50: 13.1 to 21.3 m
- Radius I-50-ON: 15.2 to 23.2 m
- Flow I-50: 1.63 to 6.84 m<sup>3</sup>/hr; 27.2 to 114.1 l/min
- Flow I-50-ON: 2.75 to 7.76 m<sup>3</sup>/hr; 45.8 to 129.4 l/min
- Recommended pressure range: 2.5 to 7.0 bar; 250 to 700 kPa
- Operating pressure range: 2.5 to 7.0 bar; 250 to 700 kPa
- Precipitation rate: 15 mm/hr approximately
- Nozzle trajectory: standard = 25°
- Warranty period: 5 years

## FACTORY-INSTALLED OPTIONS

- Reclaimed water ID

## USER-INSTALLED OPTIONS

- HSJ-1 prefabricated 1" (25 mm) PVC swing joint



### I-50 Reclaimed

Available as a factory-installed option on all models



### I-50-06-SS

Overall height: 26 cm  
Pop-up height: 15 cm  
Exposed diameter: 5 cm  
Inlet size: 1" BSP



### I-50-06-SS-ON

Overall height: 26 cm  
Pop-up height: 15 cm  
Exposed diameter: 5 cm  
Inlet size: 1" BSP



### I-50 Turf Cup Kit Option

Available as a field-installed option on all models  
P/N TURFCUPKIT140



**Below-the-turret arc adjustment**

**Robust planetary gear drive** for extreme conditions

## I-50 - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-50-06-SS = 15 cm pop-up	Adjustable arc, stainless steel riser, check valve, and 6 nozzles	<b>B</b> = BSP inlet threads <b>R</b> = Reclaimed water ID	<b>#8 to #25</b> = Factory-installed nozzle number

## I-50-ON - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-50-06-SS-ON = 15 cm pop-up	Full-circle, opposing nozzle, stainless steel riser, check valve, and 6 nozzles	<b>B</b> = BSP inlet threads <b>R</b> = Reclaimed water ID	<b>#15 to #28</b> = Factory-installed nozzle number

### Examples:

I-50-06-SS-B = 15 cm pop-up, BSP inlet threads

I-50-06-SS-ON-R-B-23 = 15 cm pop-up, full-circle opposing nozzles, reclaimed water ID, #23 nozzle, BSP inlet threads

I-50-06-SS-15-B = 15 cm Pop-up, #15 nozzle, BSP inlet threads

**I-50 STANDARD NOZZLE PERFORMANCE DATA**

Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m <sup>3</sup> /hr	l/min	■	▲
<b>08</b> ● Lt. Brown	2.5	250	13.1	1.63	27.2	19	22
	3.0	300	13.4	1.80	30.0	20	23
	3.5	350	13.7	1.94	32.3	21	24
	4.0	400	14.0	2.06	34.4	21	24
	4.5	450	14.0	2.18	36.3	22	26
	5.0	500	14.3	2.29	38.2	22	26
<b>10</b> ● Lt. Green	3.0	300	14.6	2.20	36.6	21	24
	3.5	350	14.9	2.37	39.4	21	24
	4.0	400	15.2	2.52	42.0	22	25
	4.5	450	15.5	2.67	44.5	22	25
	5.0	500	15.5	2.81	46.8	23	27
	5.5	550	15.8	2.96	49.3	24	27
<b>13</b> ● Lt. Blue	3.0	300	14.9	2.36	39.4	21	24
	3.5	350	15.2	2.55	42.6	22	25
	4.0	400	15.5	2.73	45.5	23	26
	4.5	450	15.5	2.90	48.3	24	28
	5.0	500	15.8	3.06	51.0	24	28
	5.5	550	16.2	3.23	53.9	25	29
<b>15</b> ● Grey	3.0	300	16.2	2.93	48.8	22	26
	3.5	350	16.5	3.19	53.2	24	27
	4.0	400	16.8	3.44	57.3	24	28
	4.5	450	17.1	3.67	61.2	25	29
	5.0	500	17.4	3.89	64.9	26	30
	5.5	550	18.0	4.14	68.9	26	30
<b>23</b> ● Dk. Green	3.5	350	18.6	4.48	74.6	26	30
	4.0	400	18.9	4.76	79.4	27	31
	4.5	450	19.2	5.03	83.9	27	32
	5.0	500	19.5	5.29	88.1	28	32
	5.5	550	19.8	5.56	92.7	28	33
	6.0	600	20.1	5.79	96.5	29	33
<b>25</b> ● Dk. Blue	3.5	350	19.8	4.98	83.0	25	29
	4.0	400	20.1	5.33	88.7	26	30
	4.5	450	20.4	5.65	94.2	27	31
	5.0	500	20.7	5.96	99.3	28	32
	5.5	550	21.0	6.29	104.9	28	33
	6.0	600	21.0	6.57	109.6	30	34
<b>28</b> ● Black	3.5	350	19.8	4.98	83.0	25	29
	4.0	400	20.1	5.33	88.7	26	30
	4.5	450	20.4	5.65	94.2	27	31
	5.0	500	20.7	5.96	99.3	28	32
	5.5	550	21.0	6.29	104.9	28	33
	6.0	600	21.3	6.57	109.5	30	34

**Note:**

All precipitation rates calculated for 180° operation. For the precipitation rate for a 360° sprinkler, divide by 2.

**I-50 Opposing Nozzle 360° Model**




**I-50 DUAL OPPOSING NOZZLE PERFORMANCE DATA**

Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m <sup>3</sup> /hr	l/min	■	▲
<b>15</b> ● Grey	3.0	300	15.2	2.75	45.8	12	14
	3.5	350	15.8	2.91	48.5	12	13
	4.0	400	16.2	3.06	51.0	12	14
	4.5	450	16.8	3.20	53.3	11	13
	5.0	500	17.1	3.32	55.4	11	13
	5.5	550	17.4	3.46	57.7	11	13
<b>18</b> ● Red	3.0	300	17.4	2.90	48.3	10	11
	3.5	350	17.7	3.15	52.5	10	12
	4.0	400	18.0	3.38	56.4	10	12
	4.5	450	18.0	3.61	60.1	11	13
	5.0	500	18.3	3.82	63.7	11	13
	5.5	550	18.9	4.05	67.5	11	13
<b>20</b> ● Dk. Brown	3.0	300	17.4	2.90	48.3	10	11
	3.5	350	17.7	3.15	52.5	10	12
	4.0	400	18.0	3.38	56.4	10	12
	4.5	450	18.0	3.61	60.1	11	13
	5.0	500	18.3	3.82	63.7	11	13
	5.5	550	18.9	4.05	67.5	11	13
<b>23</b> ● Dk. Green	3.0	300	19.2	4.25	70.8	12	13
	3.5	350	19.5	4.43	73.9	12	13
	4.0	400	19.5	4.43	73.9	12	13
	4.5	450	19.5	4.43	73.9	12	13
	5.0	500	19.5	4.43	73.9	12	13
	5.5	550	19.5	4.43	73.9	12	13
<b>25</b> ● Dk. Blue	3.5	350	18.3	3.98	66.2	12	14
	4.0	400	18.9	4.26	71.1	12	14
	4.5	450	19.2	4.54	75.6	12	14
	5.0	500	19.5	4.80	80.0	13	15
	5.5	550	20.1	5.08	84.7	13	15
	6.0	600	19.8	5.32	88.7	14	16
<b>28</b> ● Black	3.5	350	20.1	5.55	92.5	14	16
	4.0	400	20.1	5.55	92.5	14	16
	4.5	450	20.1	5.55	92.5	14	16
	5.0	500	20.1	5.55	92.5	14	16
	5.5	550	20.1	5.55	92.5	14	16
	6.0	600	20.1	5.55	92.5	14	16

**Note:**

Precipitation rates for the ON-Opposing Nozzles models are calculated at 360°.


**I-50 STANDARD NOZZLES**



Front



**I-50 OPPOSING NOZZLES**



Front and Back

